



ANOVA S9105 SR - 4W

Compact 4 watt surface mount LED cabinet luminaire

Application

Ideal for any residential or commercial interior space

Design Specifications

- Durable die-cast aluminium body profile
- White powder coat or satin nickel plated finish
- High efficiency LED optics
- CCT choice of 3000K / 4000K / 6000K
- 12V DC LED driver required, suitable drivers - PLUTO EGL12V/6W, PLUTO 15DV, 40DV, 60DV

Performance

- Dimmable - **NO**



Technical Specification

Product	Model No.	Input Voltage (V/DC)	Power (W)	Lumens (lm)	CCT (K)	CRI
	S9105WW SR/WH	12	4	280	3000	80
	S9105DL SR/WH	12	4	280	6000	80
	S9105WW SR/SN	12	4	280	3000	80
	S9105DL SR/SN	12	4	280	6000	80




Beam Angle (°)	Dimmable	Diameter (mm)	Dim (mm)	Body Colour
90	NO	77	27(H)	WHITE
90	NO	77	27(H)	WHITE
90	NO	77	27(H)	SATIN NICKEL
90	NO	77	27(H)	SATIN NICKEL

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions

S9105 SR



Photometric Data

Unit: cd C0/C180 — C90/C270 —






Image courtesy of QCE,
photography Indie Lane Tourquay

**DID
YOU
KNOW** ?

Before selecting a luminaire, look for the marks of Compliance and Safety. Starting with the RCM mark, this signals that the product has been tested to all relevant Australian Safety standards, to ensure the product delivers its designed safety performance.